

# PARASOUND NEW CLASSIC

New Products Q4 2005

## D 200 Universal Disc Player



- HDMI digital video/audio output with HDCP
- 480p / 720p / 1080i selectable scan rate
- Simultaneous progressive scan component video output and interlaced composite video output
- Faroudja DCDI processing for precision progressive scan
- DVD-Audio and SACD multi-channel
- SACD DSD bit stream goes directly to audio DAC
- DVD-A, SACD with bass management
- DVD±R/RW, CD-R/RW compatible
- MP-3, JPEG, WMA, DivX playback, Kodak Picture CD playback
- 192 kHz / 24-Bit audio DACs
- 216 MHz / 12 bit precision video DAC
- Pure Black mode with black level adjustment, 7.5 IRE or 0 IRE
- Two s-video and two composite video output jacks
- Gold-plated 5.1 channel analog audio output jacks, two extra L, R output jacks
- Coaxial and optical digital audio outputs
- Defeatable video & digital audio circuits for purest analog audio
- RS-232C two-way communication port with DB9 connector
- Easy to use remote control handset with glow-in-the-dark buttons
- External IR repeater input and looping output jacks
- Detachable IEC AC power cord
- 115v / 230v operation
- Heavy duty 3U chassis, rack mounts with RMK33 (not included)

## P 2000 Preamplifier



- 7 stereo inputs (1 phono/line selectable input)
- Bass and treble and controls can be defeated with remote control
- IR remote control handset included
- Record / Fixed output jacks
- Extra output jacks can be switched stereo or mono full range output to facilitate subwoofer connection
- Headphone output
- Auto or manual turn on, auto defeats front panel Power button
- 12 Volt DC trigger input and output jacks
- External IR repeater input jack and looping output jack
- RS-232C 2-way Communication
- Rear panel selectable 120V or 230V power
- Frequency response 10 Hz - 100 kHz, +0/-3 dB, 10 Hz - 50 kHz, +0/-0.75 dB
- Total harmonic distortion: 0.003%
- S/N ratio: 112 dB, input shorted, IHF A-weighted; 92 dB, input shorted, unweighted
- Input impedance: 15 k $\Omega$
- Input sensitivity: 200 mV for 1 V output
- Maximum output: > 7.6 V
- Crosstalk: over 95 dB at 1 kHz; 76 dB at 20 kHz
- Precision motorized analog volume control potentiometer
- Detachable IEC AC power cord
- Switchable for 115v / 230v operation

PARASOUND  
NEW CLASSIC

Parasound Products, Inc. 950 Battery Street, San Francisco, CA 94111  
415-397-7100 / FAX 415-397-0144 [www.parasound.com](http://www.parasound.com)